






# DATASHEET






HELIOS-35<sup>+</sup>

## BASE UNIT HELIOS-35<sup>+</sup>

Complete of supply cable (15m), central power unit (integrated cooling system), power cable (10m), heating head.  
You just need to choose your inductors to start heating immediately!

<b>POWER</b>	30 KVA
<b>FREQUENCY RANGE</b>	5 ÷ 35 KHz
<b>SUPPLY</b>	380-440V AC-3PH-50Hz/60Hz
<b>ELECTRICAL PLUG</b>	32A 3P+E
<b>WEIGHT</b>	205 Kg
<b>DIMENSIONS</b>	1000 x 830 x H 1000mm
<b>COOLING SYSTEM</b>	 Integrated
<b>FEATURES</b>	 4.3" Color graphic display  Power regulation  Diagnostics (faults detection system)  USB Port
<b>CERTIFICATIONS</b>	CE Compliance, 2006/42 EC Machinery Directive, 2014/30 EU Electromagnetic Compatibility

## OPTIONS AVAILABLE

<b>HELIOS-35+_T</b>	 <b>TIMER</b> to set the desired heating time
<b>HELIOS-35+_SMART</b>	 <b>4.0 INDUSTRY</b> to communicate remotely via Wi-Fi or Modem (SIM excluded) connections. This option, through the provided "Helios Manager" software will allow to: - Remotely set up working plans - Record heating data - Generate performance reports
<b>HELIOS-35+_S</b>	 <b>TEMPERATURE SENSOR</b> To set up the maximum desired temperature

